

View Online at <https://aerobasegroup.com/nsn/6625-00-539-9279>

**Overall Length:**

14.750 inches

**Overall Height:**

15.000 inches

**Overall Width:**

17.125 inches

**Current Type:**

Ac

**Frequency Rating:**

Between 50.0 hertz and 450.0 hertz

**Accessory Components And Quantity:**

11 adapters, 2 rf cables, 2 test prods

**Voltage Rating:**

Between 105.0 volts and 125.0 volts

**Beam Quantity:**

1

**Mounting Method:**

Portable

**Screen Size:**

3 in.

**Sweep Circuits:**

Included

**Generator Driven Feature:**

Not included

**Sweep Frequency Range:**

+8.000/+600000.000 hertz

**Single Trigger Sweep Duration:**

Between 0.00125 milliseconds and 125.00000 milliseconds

**Trigger Sweep Polarity Switch:**

Not included

**Expanded Sweep:**

Not provided

**Amplifier Deflection Sensitivity Provision:**

Provided

**Vertical Deflection Sensitivity Voltage Rating:**

35.0 millivolts rms per inch

**Horizontal Deflection Sensitivity Voltage Rating:**

4.0 volts any acceptable outside diameter

**Input Intensity Modulation Feature:**

Not provided

**Plate Direct Connection Deflection Sensitivity Provision:**

Not provided

**Frequency Response Rating:**

Provided

**X-axis Frequency Response Rating:**

Between 0.0005 kilohertz and 700.0000 kilohertz

**Y-axis Frequency Response Rating:**

Between 0.0000015 megahertz and 10.0000000 megahertz

**Z-axis Frequency Response Rating:**

Between 0.00005 megahertz and 10.00000 megahertz

**Amplifier Input Impedance Rating Provision:**

Provided

**X-axis Input Impedance Rating:**

5.6 megohms

**Y-axis Input Impedance Rating:**

300.0 kilohms

**Z-axis Input Impedance Rating:**

56.0 kilohms

**Calibrated Screen Scale:**

Not included

**Trace Storage Tube:**

Not included

**Camera Recording Device Accommodation:**

Not provided

**Phase:**

Single

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T320-g