

View Online at <https://aerobasegroup.com/nsn/6625-00-539-9642>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

2.850 inches

**Mounting Hole Diameter:**

Between 0.143 inches and 0.157 inches

**Scale Division Quantity:**

40 single indicator single range

**Overall Diameter:**

3.510 inches

**Environmental Protection:**

Heat resistant and humidity resistant and shock resistant and vibration resistant and watertight

**Mounting Bolt Circle Diameter:**

3.160 inches

**Furnished Items And Quantity:**

Nut 7, washer 7

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.660 inches

**Meter Body Diameter Behind Mounting Flange:**

2.800 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Mounting Facility Type And Quantity:**

1 flange and 3 screw and 3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0/+20.0 milliamperes, dc single indicator single range

**Features Provided:**

Magnetic shield and zero adjuster

**Circuit Attachment Method And Quantity:**

2 solder lug and 2 threaded stud

**Special Features:**

Ruggedized

**Special Markings:**

Viewed from the rear the left terminal is positive and marked with a plus sign; meter marked iaw mil-std-1285

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel semigloss

**Special Test Features:**

law mil-std-202

**Surface Treatment Specification:**

Mil-f-14072 military specification single treatment response

**Style Designator:**

Round flush mtg

**Test Data Document:**

81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-m-10304/12 government specification

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0

**Mil-std (military Standard):**

Mil-f-14072 spec.