NSN 6625-00-539-9642

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-539-9642

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.850 inches
Mounting Hole Diameter:
Between 0.143 inches and 0.157 inches
Scale Division Quantity:
40 single indicator single range
Overall Diameter:
3.510 inches
Environmental Protection:
Heat resistant and humidity resistant and shock resistant and vibration resistant and watertight
Mounting Bolt Circle Diameter:
3.160 inches
Furnished Items And Quantity:
Nut 7, washer 7
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.660 inches
Meter Body Diameter Behind Mounting Flange:
2.800 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range

1 flange and 3 screw and 3 unthreaded hole

Mounting Facility Type And Quantity:

Black single indicator single range

Pointer Color:

NSN 6625-00-539-9642

Ammeter - Page 2 of 2

Mil-f-14072 spec.



Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+20.0 milliamperes, dc single indicator single range
Features Provided:
Magnetic shield and zero adjuster
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
Ruggedized
Special Markings:
Viewed from the rear the left terminal is positive and marked with a plus sign; meter marked iaw mil-std-1285
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel semigloss
Special Test Features:
law mil-std-202
Surface Treatment Specification:
Mil-f-14072 military specification single treatment response
Style Designator:
Round flush mtg
Test Data Document:
81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-m-10304/12 government specification
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0
Mil-std (military Standard):