NSN 6625-00-542-0830

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-542-0830

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.820 inches
Mounting Hole Diameter:
0.138 inches
Scale Division Quantity:
2 single indicator all ranges
Overall Diameter:
3.510 inches
Environmental Protection:
Heat resistant and humidity resistant and shock resistant and vibration resistant
Mounting Bolt Circle Diameter:
3.160 inches
Furnished Items And Quantity:
Nut 3; washer 3
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
50.0 microamperes
Dial Scale Marking Color:
Black and blue and white single indicator all ranges
Accuracy In Percent:
-2.0 to 2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.660 inches
Meter Body Diameter Behind Mounting Flange:
2.800 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator all ranges
Pointer Color:
Black single indicator all ranges
Power Source:

External

NSN 6625-00-542-0830 Voltmeter - Page 2 of 2



Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Linear single indicator all ranges
Measurement Range:
150.0 to 450.0 volts, dc single indicator 3rd range
Features Provided:
Zero adjuster
Circuit Attachment Method And Quantity:
2 solder lug
Special Features:
Ruggedized
Special Markings:
White band with black letter a at neg 50 to neg 39.3 ua; white band with black letter b at neg 15 to 15 ua; white band with black letter c a
41.9 to 46.3 ua; blue band with black letter d at bdt of arc at 38.2 to 50 ua
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Special Test Features:
Conforms to mil-m-10304
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A310a0