

View Online at <https://aerobasegroup.com/nsn/6625-00-542-1404>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.150 inches

Mounting Hole Diameter:

0.125 inches

Mounting Stud Length:

Between 0.375 inches and 0.625 inches

Overall Diameter:

2.695 inches

Mounting Bolt Circle Diameter:

2.440 inches

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+25.000/+125.000 hertz

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.750 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving iron vane

Background Color:

Black single indicator single range

Mounting Facility Type And Quantity:

3 flange

Measurement Range:

+0.0/+150.0 volts, ac single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Markings:

Red line at 120v

Radioactive Content:

Contains radioactive material

Style Designator:

Round flush mtg

Specification Or Standard:

Mr26s150acvvr type

Departure From Cited Designator:

As modified by reply to pac mark

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0