## NSN 6625-00-542-1556

Voltmeter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-542-1556

Circuit Current For Which Designed:
Ac
Overall Length:
2.430 inches
Overall Diameter:
3.500 inches
Mounting Bolt Circle Diameter:
3.124 inches
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Frequency Response Range:
+0.000/+400.000 hertz
Dial Scale Marking Color:
Black all indicators single range
Accuracy In Percent:
-2.0/+2.0 at full scale all indicators all ranges
Meter Depth Behind Mounting Flange:
2.031 inches
Meter Body Diameter Behind Mounting Flange:
Meter Body Diameter Behind Mounting Flange: 2.690 inches
2.690 inches
2.690 inches  Movement Type:
2.690 inches  Movement Type:  Moving iron vane
2.690 inches  Movement Type:  Moving iron vane  Measurement Range:
2.690 inches  Movement Type:  Moving iron vane  Measurement Range: +0.0/+300.0 volts, ac 2nd indicator single range
2.690 inches  Movement Type:  Moving iron vane  Measurement Range: +0.0/+300.0 volts, ac 2nd indicator single range  Circuit Attachment Method And Quantity:
2.690 inches  Movement Type:  Moving iron vane  Measurement Range: +0.0/+300.0 volts, ac 2nd indicator single range  Circuit Attachment Method And Quantity: 3 solder stud
2.690 inches  Movement Type:  Moving iron vane  Measurement Range: +0.0/+300.0 volts, ac 2nd indicator single range  Circuit Attachment Method And Quantity: 3 solder stud  Material:
2.690 inches  Movement Type:  Moving iron vane  Measurement Range: +0.0/+300.0 volts, ac 2nd indicator single range  Circuit Attachment Method And Quantity: 3 solder stud  Material:  Plastic
2.690 inches  Movement Type:  Moving iron vane  Measurement Range: +0.0/+300.0 volts, ac 2nd indicator single range  Circuit Attachment Method And Quantity: 3 solder stud  Material:  Plastic  Style Designator:
2.690 inches  Movement Type:  Moving iron vane  Measurement Range: +0.0/+300.0 volts, ac 2nd indicator single range  Circuit Attachment Method And Quantity: 3 solder stud  Material:  Plastic  Style Designator:  Round flush mtg
2.690 inches  Movement Type:  Moving iron vane  Measurement Range: +0.0/+300.0 volts, ac 2nd indicator single range  Circuit Attachment Method And Quantity: 3 solder stud  Material:  Plastic  Style Designator:  Round flush mtg  Shelf Life:
2.690 inches  Movement Type:  Moving iron vane  Measurement Range: +0.0/+300.0 volts, ac 2nd indicator single range  Circuit Attachment Method And Quantity: 3 solder stud  Material:  Plastic  Style Designator:  Round flush mtg  Shelf Life:  N/a
2.690 inches  Movement Type:  Moving iron vane  Measurement Range: +0.0/+300.0 volts, ac 2nd indicator single range  Circuit Attachment Method And Quantity: 3 solder stud  Material:  Plastic  Style Designator:  Round flush mtg  Shelf Life:  N/a
2.690 inches  Movement Type:  Moving iron vane  Measurement Range: +0.0/+300.0 volts, ac 2nd indicator single range  Circuit Attachment Method And Quantity: 3 solder stud  Material: Plastic  Style Designator: Round flush mtg  Shelf Life: N/a  Unit Of Measure:
2.690 inches  Movement Type:  Moving iron vane  Measurement Range: +0.0/+300.0 volts, ac 2nd indicator single range  Circuit Attachment Method And Quantity: 3 solder stud  Material: Plastic  Style Designator: Round flush mtg  Shelf Life: N/a  Unit Of Measure:  Demilitarization: