

View Online at <https://aerobasegroup.com/nsn/6625-00-542-1558>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Reliability Indicator:

Not established

Overall Length:

2.150 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

30 single indicator single range

Overall Diameter:

2.695 inches

Mounting Bolt Circle Diameter:

2.440 inches

End Application:

Aircraft stratolifter c-135, eagle f-15, thunderbolt ii a-10, advanced air traffic control and landing system, joint surveillance syste (jss) region operations control center(rocc), support equipment aircraft a-10, c-5, navstar global positioning system(control segment)

Furnished Items And Quantity:

Screw 4.40 thd 0.500 in. Long, rd head, black 3; washer lock 3; nut hex 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.750 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

1 flange and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+150.0 volts, ac single indicator single range

Features Provided:

Magnetic shield

Criticality Code Justification:

Feat

Movement Suspension Method:

Metal pivot base

Circuit Attachment Method And Quantity:

2 binding post

Special Features:

Weapon system essential

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

FiiG:

A310a0