

View Online at <https://aerobasegroup.com/nsn/6625-00-542-1773>

Circuit Current For Which Designed:

Ac

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.562 inches

Overall Height:

4.203 inches

Overall Width:

4.656 inches

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-5.0/+5.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.000 inches

Meter Body Diameter Behind Mounting Flange:

2.750 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Mounting Facility Type And Quantity:

4 threaded stud

Measurement Range:

+0.0/+300.0 volts, ac single indicator single range

Mounting Stud Diameter:

0.138 inches

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Style Designator:

Rectangular flush mtg

Reference Number Differentiating Characteristics:

As differentiated by the measurement range per indicator requirement

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0