

View Online at <https://aerobasegroup.com/nsn/6625-00-543-7662>

Circuit Current For Which Designed:

Ac

Overall Length:

1.710 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.740 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.373 inches

Overall Height:

3.500 inches

Overall Width:

3.500 inches

Scale Division Quantity:

45 single indicator single range

Mounting Stud Length:

0.500 inches

Shortest Horizontal Distance Between Mounting Centers:

1.370 inches

Furnished Items And Quantity:

Mounting hardware 1 set

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud triangular

Frequency Response Range:

+25.000/+400.000 hertz

Sensitivity Rating:

5.0 amperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.210 inches

Meter Body Diameter Behind Mounting Flange:

2.700 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+100.0 amperes, ac single indicator single range

Mounting Stud Diameter:

0.112 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Elec, elect. Properties measuring and test instruments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0