NSN 6625-00-546-6606

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-546-6606

Circuit Current For Which Designed:
Ac
Overall Length:
3.218 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.375 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.375 inches
Overall Height:
4.328 inches
Overall Width:
4.328 inches
Scale Division Quantity:
45 single indicator single range
Mounting Stud Length:
0.625 inches
Environmental Protection:
Dust resistant and humidity resistant and shock resistant and vibration resistant
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Frequency Response Range:
+40.000/+70.000 hertz
Sensitivity Rating:
5000.0 milliamperes
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-1.0/+1.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
2.406 inches
Meter Body Diameter Behind Mounting Flange:
3.968 inches
Movement Type:
Moving iron vane
Background Color:
White single indicator single range

Pointer Color:

Black single indicator single range

NSN 6625-00-546-6606

Ammeter - Page 2 of 2



Power Source:
External
Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+500.0 amperes, ac single indicator single range
Mounting Stud Diameter:
0.250 inches
Scale Selection Method:
Terminal
Features Provided:
Zero adjuster
Movement Suspension Method:
Taut band
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Ruggedized
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Special Test Features:
Complies with ansi specification c-39.1
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0