NSN 6625-00-551-7931

Incandescent Readout - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-551-7931

General Description:

No

Q0.408 in. Min 0.452 in. Maximum Ig, 0.456 in. Min 0.476 in. Maximum h, 0.296 in. Min 0.316 in. Maximum w, 4.0v, dc, 16.5 porm 3.5 ma
current/segment, 8000 porm 4000 ft-lamberts brightness, legend digital, m55 to p85 degrees c operating temp

Q0.408 in. Min 0.452 in. Maximum Ig, 0.456 in. Min 0.476 in. Maximum h, 0.296 in. Min 0.316 in. Maximum w, 4.0v, dc, 16.5 porm 3.5 maximum h, 0.296 in. Min 0.452 in. Maximum w, 4.0v, dc, 16.5 porm 3.5 maximum h, 0.296 in. Min 0.476 in. Maximum h, 0.296 in. Min 0.316 in. Maximum w, 4.0v, dc, 16.5 porm 3.5 maximum h, 0.296 in. Min 0.476 in. Maximum h, 0.296 in. Min 0.316 in. Maximum w, 4.0v, dc, 16.5 porm 3.5 maximum h, 0.296 in. Min 0.476 in. Maximum h, 0.296 in. Min 0.316 in. Maximum w, 4.0v, dc, 16.5 porm 3.5 maximum h, 0.296 in. Min 0.476 in. Maximum h, 0.296 in. Min 0.316 in. Maximum w, 4.0v, dc, 16.5 porm 3.5 maximum h, 0.296 in. Min 0.316 in. Maximum w, 4.0v, dc, 16.5 porm 3.5 maximum w, 4.0v, dc, 16.5
current/segment, 8000 porm 4000 ft-lamberts brightness, legend digital, m55 to p85 degrees c operating temp
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: