NSN 6625-00-552-0144

Voltmeter - Page 1 of 2



| Volumeter - Fage 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/6625-00-552-0144 |
| Circuit Current For Which Designed: |
| Dc |
| Overall Length: |
| 2.850 inches |
| Mounting Hole Diameter: |
| 0.150 inches |
| Scale Division Quantity: |
| 30 single indicator single range |
| Overall Diameter: |
| 3.500 inches |
| Mounting Bolt Circle Diameter: |
| 3.160 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Sensitivity Rating: |
| 1000.0 ohms per volt |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0 to 2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.750 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.800 inches |
| Movement Type: |

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 15.0 volts, dc single indicator single range

NSN 6625-00-552-0144Voltmeter - Page 2 of 2



| Scale Selection Method: |
|---|
| Terminal |
| Features Provided: |
| Magnetic shield and zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 binding post |
| Special Features: |
| Ruggedized |
| Special Markings: |
| Red line at 11.5 v |
| Material: |
| Plastic |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |
| |
| |