

View Online at <https://aerobasegroup.com/nsn/6625-00-553-0329>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Length:

1.526 inches

Overall Height:

5.580 inches

Overall Width:

4.416 inches

Scale Division Quantity:

40 single indicator 1st range

Mounting Stud Length:

1.500 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Distance Between Mounting Facility Centers:

3.336 inches

Furnished Items And Quantity:

Nut 4; lockwasher 4; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

2 threaded stud

Scale Graduation Type:

Nonlinear single indicator 2nd range

Measurement Range:

+0.0 to 40.0 decibels single indicator 1st range

Mounting Stud Diameter:

0.187 inches

Scale Selection Method:

Terminal

Features Provided:

Nonglare glass and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Special Markings:

Front side, left corner, h

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Fan shape surface mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0