

View Online at <https://aerobasegroup.com/nsn/6625-00-553-0433>

Mounting Type:

Case

Overall Length:

21.062 inches

Overall Height:

16.500 inches

Overall Width:

13.500 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 100.0 hertz

Case Material:

Aluminum and wood

Case Surface Treatment:

Enameled

Frequency Range Rating:

+0.900/+2.100 gigahertz

Accessory Component Quantity:

3 and 3 and 3 and 1 and 1 and 1 and 1 and 1 and 1

Accessory Controlling Agency:

Jetds; jetds; jetds; jetds; jetds; jetds; jetds; jetds; jetds

Accessory Identifying Number:

Ug-201/u type no. And ug-255/u type no. And ug-273/u type no. And cx-3277/u type no. And cg-546/u type no. And ts-419/u type no. And cy-686/u ro cy-686a/u type no. And cg409/u-72 in. Type no. And cg-409/u-96 type no.

Output Impedance Rating:

50.0 ohms

Voltage Rating:

115.0 volts

Frequency Band Quantity:

1

Modulation Type:

Pulse

Accessory Component Name:

Adapter 1; adapter 1; adapter 1; power cable 1; rf cable 1; signal generator1; transit case 1; eo cable 1; cable 1

Crystal Controlled Feature:

Not provided

Calibrated Signal Output Range:

0.2 uv to 0.16 v

Signal Output Constancy:

Porm 2.0 db maximum variation throughout freq range

Modulator Location:

External

Pulse Repetition Frequency Rating:

Between 0.4 kilohertz and 4.0 kilohertz

Modulation Degree:

100.0 percent

Phase:

Single

Functional Description:

Provides accurately pulse modulated and cw radio freq signals for testing radar and radio receivers requiring less than 0.8e-3 watts of rf power

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T320-j