NSN 6625-00-553-0613

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-553-0613

Circuit Current For Which Designed: Dc Overall Length: 2.067 inches Mounting Hole Diameter: 0.125 inches Scale Division Quantity: 60 single indicator single range Overall Diameter: 2.695 inches Mounting Bolt Circle Diameter: 2.440 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.687 inches
Overall Length: 2.067 inches Mounting Hole Diameter: 0.125 inches Scale Division Quantity: 60 single indicator single range Overall Diameter: 2.695 inches Mounting Bolt Circle Diameter: 2.440 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Mounting Hole Diameter: 0.125 inches Scale Division Quantity: 60 single indicator single range Overall Diameter: 2.695 inches Mounting Bolt Circle Diameter: 2.440 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Mounting Hole Diameter: 0.125 inches Scale Division Quantity: 60 single indicator single range Overall Diameter: 2.695 inches Mounting Bolt Circle Diameter: 2.440 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
0.125 inches Scale Division Quantity: 60 single indicator single range Overall Diameter: 2.695 inches Mounting Bolt Circle Diameter: 2.440 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Scale Division Quantity: 60 single indicator single range Overall Diameter: 2.695 inches Mounting Bolt Circle Diameter: 2.440 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Overall Diameter: 2.695 inches Mounting Bolt Circle Diameter: 2.440 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Overall Diameter: 2.695 inches Mounting Bolt Circle Diameter: 2.440 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
2.695 inches Mounting Bolt Circle Diameter: 2.440 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Mounting Bolt Circle Diameter: 2.440 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
2.440 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Three hole/stud bolt circle Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
-2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Meter Depth Behind Mounting Flange:
1.687 inches
Meter Body Diameter Behind Mounting Flange:
2.210 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Mounting Facility Type And Quantity:
3 unthreaded hole
Features Provided:
Magnetic shield
Circuit Attachment Method And Quantity:
2 solderless lug
Special Features:
External shunt required, ruggedized
Style Designator:
Round flush mtg
Shelf Life:
N/a

NSN 6625-00-553-0613

Ammeter - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A310a0