

View Online at <https://aerobasegroup.com/nsn/6625-00-553-1203>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

3.090 inches

**Overall Height:**

4.250 inches

**Overall Width:**

4.000 inches

**Frequency Rating:**

60.0 hertz

**Environmental Protection:**

Shock resistant and vibration resistant

**Furnished Items And Quantity:**

Screw 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Frequency Response Range:**

+57.000 to 63.000 hertz

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.0 to 1.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

2.156 inches

**Meter Body Width Behind Mounting Flange:**

3.700 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

2 clamp and 4 screw

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+0.0 to 250.0 volts, ac single indicator single range

**Meter Body Height Behind Mounting Flange:**

3.953 inches

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 solder lug and 2 threaded stud

**Phase:**

Single

**Special Features:**

Ruggedized

**Material:**

Plastic phenolic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A310a0