

View Online at <https://aerobasegroup.com/nsn/6625-00-553-1203>

Circuit Current For Which Designed:

Ac

Overall Length:

3.090 inches

Overall Height:

4.250 inches

Overall Width:

4.000 inches

Frequency Rating:

60.0 hertz

Environmental Protection:

Shock resistant and vibration resistant

Furnished Items And Quantity:

Screw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Frequency Response Range:

+57.000 to 63.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0 to 1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.156 inches

Meter Body Width Behind Mounting Flange:

3.700 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 clamp and 4 screw

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0 to 250.0 volts, ac single indicator single range

Meter Body Height Behind Mounting Flange:

3.953 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Phase:

Single

Special Features:

Ruggedized

Material:

Plastic phenolic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0