

View Online at <https://aerobasegroup.com/nsn/6625-00-553-7387>

**Width:**

Between 10.800 inches and 22.000 inches

**Length:**

Between 7.870 inches and 21.600 inches

**Ac Voltage Rating:**

230.0 volts

**Frequency Rating:**

50.0 hertz

**Major Components:**

Frequency meter; frequency converter; timer; frequency meter case; timer case; radio frequency cable assembly; radio frequency cable assembly; radio frequency cable assembly; power cable assembly; adapter connector; adapter connector; adapter connector; adapter connector; adapter connector; adapter connector; adapter connector; adapter connector; adapter connector

**Accessory Component Quantity:**

1 and 1 and 1 and 1 and 1 and 1 and 1 and 2 and 1 and 2 and 2 and 2 and 2 and 2 and 2 and 2 and 2

**Accessory Controlling Agency:**

Jcens

**Accessory Identifying Number:**

Fr-38b/u type no. And mx-16371/u type no. And mx-16361/u type no. And cy-1424/usm-26a type no. And cy-1563/usm-26a type no. And cx-2928/usm-26a type no. And cx-2927/usm-26a type no. And cg-530/u type no. And cx-3135/u type no. And ug0201a/u part no. And ug-225/u part no. And ug-273/u part no. And ug-282/u part no. And ug-349a/u part no. And ug-914/u part no. And ug-1034/u part no. And ug-1035/u part no.

**Internal Battery Accommodation:**

Not included

**Material And Location:**

Aluminum carrying case

**Test Type For Which Designed:**

Frequency measurements; time interval measurements; period measurements

**Operating Test Capability:**

Frequency measurement, range 10 cps to 10 mc with frequency meter, input 1.0 v rms min, range 10 cps to 100 mc with frequency converter, input 0.1 v rms min from 10 cps to 10 mc, range 10 cps to 100 mc with frequency converter, input 10.0 mv rms min from 10 mc to 100 mc; frequency meter with timer, range 0.1 usec to 10 million sec, input 1.0 v peak min

**Phase:**

Single

**Height:**

Between 7.870 inches and 22.300 inches

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T228-a