NSN 6625-00-553-8852

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-553-8852

Circuit Current For Which Designed:
Ac
Dielectric Withstanding Voltage In Volts:
2000.0
Overall Length:
2.030 inches
Mounting Hole Diameter:
0.125 inches
Frequency Rating:
60.0 hertz
Overall Diameter:
2.695 inches
Environmental Protection:
Shock resistant and vibration resistant
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Term hdw 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
500.0 milliamperes
Dial Scale Marking Color:
Black single indicator single range and green single indicator single range and red single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.170 inches
Meter Body Diameter Behind Mounting Flange:
2.150 inches
Movement Type:
Moving iron vane
Background Color:
White single indicator single range
Pointer Color:

Black single indicator single range

NSN 6625-00-553-8852

Special Scale Meter - Page 2 of 2



Scale Marking:
Zer0; level set; overload; colored bands
Mounting Facility Type And Quantity:
3 unthreaded hole
Scale Graduation Type:
Nonlinear single indicator single range
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Phase:
Single
Special Features:
Internally rectified
Special Markings:
Level set has green band; overload has red band
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel
Special Test Features:
Conforms to mil-m-10304
Style Designator:
Round flush mtg
Supplementary Features:
3100 amps impedance at 1 vrms, 1 khz
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A310a0