

View Online at <https://aerobasegroup.com/nsn/6625-00-556-1878>

Circuit Current For Which Designed:

Ac

Overall Length:

2.297 inches

Mounting Hole Diameter:

0.125 inches

Frequency Rating:

50.0 hertz

Overall Diameter:

2.688 inches

Mounting Bolt Circle Diameter:

2.438 inches

Furnished Items And Quantity:

Term. Hdw 2

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+48.000 to 52.000 hertz

Resonant Reed Quantity:

5

Meter Depth Behind Mounting Flange:

1.375 inches

Meter Body Diameter Behind Mounting Flange:

2.156 inches

Movement Type:

Vibrating reed

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Measurement Range:

+48.0 to 52.0 hertz single indicator single range

Scale Selection Method:

Terminal

Circuit Attachment Method And Quantity:

2 threaded stud

Phase:

Single

Special Markings:

Cycles

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0