## NSN 6625-00-557-0227

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-557-0227

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
1500.0
Overall Length:
2.053 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.235 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.235 inches
Overall Height:
3.150 inches
Overall Width:
3.034 inches
Scale Division Quantity:
50 single indicator all ranges
Mounting Stud Length:
0.500 inches
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Furnished Items And Quantity:
Nut 6; lockwasher 6; markgon front, use with external resistor
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
1.0 milliamperes
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.339 inches
Meter Body Diameter Behind Mounting Flange:
2.741 inches
Movement Type:

Background Color:

Moving coil, permanent magnet

White single indicator all ranges

## NSN 6625-00-557-0227

Ammeter - Page 2 of 2



Pointer Color:
Black single indicator all ranges
Power Source:
External
Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Linear single indicator all ranges
Measurement Range:
+0.0/+500.0 milliamperes, dc single indicator 3rd range
Mounting Stud Diameter:
0.109 inches
Scale Selection Method:
Terminal
Features Provided:
External shunting and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Ruggedized
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Special Test Features:
Complies with mil-m-10304
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A310a0