

View Online at <https://aerobasegroup.com/nsn/6625-00-557-0249>

Overall Length:

16.937 inches

Overall Height:

9.375 inches

Overall Width:

6.625 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Accessory Components And Quantity:

2 adapters, 2 cables, 3 probes, 1 scale, calibrated

Voltage Rating:

115.0 volts

Beam Quantity:

1

Mounting Method:

Portable

Screen Size:

3 in.

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Sweep Circuit Type:

Any acceptable

Sweep Frequency Range:

+45.000/+55000.000 hertz

Single Trigger Sweep Duration:

Between 1.0 microseconds and 2.0 microseconds

Trigger Sweep Voltage Amplitude Rating:

100.0 volts

Trigger Sweep Polarity Switch:

Included

Trigger Sweep Marker Intervals:

10000, 1000, 100, 10, and 1 usec

Expanded Sweep:

Not provided

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

100.0 millivolts rms per inch

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Provided

Direct Connection Vertical Deflection Sensitivity Voltage Rating:

15.0 volts cw outside diameter and 18.0 volts peak outside diameter

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

Between 10.0 hertz and 4000000.0 hertz

Y-axis Frequency Response Rating:

Between 10.0 hertz and 7000000.0 hertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.0 megohms

Y-axis Input Impedance Rating:

1.5 megohms

Calibrated Screen Scale:

Not included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Specification Or Standard:

An/usm-32 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-g