

View Online at <https://aerobasegroup.com/nsn/6625-00-557-0294>

Circuit Current For Which Designed:

Dc

Reliability Indicator:

Not established

Overall Length:

2.063 inches

Mounting Hole Diameter:

0.156 inches

Scale Division Quantity:

40 single indicator single range

Overall Diameter:

3.500 inches

Mounting Bolt Circle Diameter:

3.156 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

1000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.704 inches

Meter Body Diameter Behind Mounting Flange:

2.672 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 40.0 volts, dc single indicator single range

Features Provided:

Magnetic shield

Circuit Attachment Method And Quantity:

2 solder stud

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0