## NSN 6625-00-557-0311



Signal Generator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6625-00-557-0311 **Mounting Type:** Case **Overall Length:** 18.000 inches **Overall Height:** 12.000 inches **Overall Width:** 12.000 inches **Current Type:** Ac Frequency Rating: Between 0.05 kilohertz and 1.0 kilohertz **Case Material:** Aluminum **Case Surface Treatment:** Enameled Frequency Range Rating: +20.000/+100.000 megahertz **Accessory Component Quantity: Accessory Controlling Agency: Jetds Accessory Identifying Number:** Sg-12/u type no. And cy-1217/u type no. **Joint Electronics Type Designation System Item Name:** Generator, signal Joint Electronics Type Designation System Item Type Number: Type no. An/urm48// **Internal Battery Accommodation:** Not included

Voltage Rating:

115.0 volts and 230.0 volts

**Modulation Type:** 

Fm

**Accessory Component Name:** 

Generator signal 1; case 1

**Calibration Accuracy Rating:** 

Porm 5 pct accuracy of calibration

**Fixed Frequency Quantity:** 

**Crystal Controlled Feature:** 

Provided

## **NSN 6625-00-557-0311**Signal Generator - Page 2 of 2



Calibrated Signal Output Range:
0.05 uv to 0.01 uv
Signal Output Constancy:
Porm 2.0 db maximum variation throughout freq range
Modulator Location:
Internal
Modulated Frequency Rating:
1.0 kilohertz
Phase:
Single
Special Features:
Freq deviation 0-50000hz on freqs from 19.7 to 56e6; 0-100000hz on freqs from 46 to 102e6; external modulation 100-20000hz
Functional Description:
Provides rf signals for aligning and trouble shooting various radio sets. Spot frequencies change from 1.37 to 15hz when sg12a/u is used
Fsc Application Data:
Test set, radar, except specially designed
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Т320-ј