NSN 6625-00-557-5553

Voltmeter - Page 1 of 2

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-557-5553

| Dc |
|---|
| Overall Length: |
| 4.250 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.040 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.670 inches |
| Overall Height: |
| 2.050 inches |
| Overall Width: |
| 3.940 inches |
| Scale Division Quantity: |
| 1 single indicator single range |
| Mounting Stud Length: |
| 0.500 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Sensitivity Rating: |
| 1.0 milliamperes |
| Dial Scale Marking Color: |
| Black single indicator all ranges |
| Accuracy In Percent: |
| -3.0 to 3.0 at full scale single indicator all ranges |
| Meter Depth Behind Mounting Flange: |
| 3.825 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 1.725 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator all ranges |
| Pointer Color: |
| Black single indicator all ranges |
| Power Source: |
| External |

4 threaded stud

Mounting Facility Type And Quantity:

NSN 6625-00-557-5553 Voltmeter - Page 2 of 2



| Scale Graduation Type: |
|---|
| Nonlinear single indicator all ranges |
| Measurement Range: |
| -10.0 to 50.0 decibels single indicator 1st range |
| Mounting Stud Diameter: |
| 0.138 inches |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Material: |
| Plastic |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Rectangular flush mtg |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Filg: |
| A310a0 |