

View Online at <https://aerobasegroup.com/nsn/6625-00-557-5826>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.820 inches

Scale Division Quantity:

75 single indicator single range

Mounting Stud Length:

0.500 inches

Overall Diameter:

3.510 inches

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Washers 7, nuts 7

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.660 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+150.0 milliamperes, ac single indicator single range

Mounting Stud Diameter:

0.150 inches

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round semi-flush mtg

Test Data Document:

81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0