

View Online at <https://aerobasegroup.com/nsn/6625-00-568-4476>

Circuit Current For Which Designed:

Dc

Overall Length:

Between 2.438 inches and 2.563 inches

Scale Division Quantity:

4 single indicator 2nd range

Furnished Items And Quantity:

Nut 8; washer 12

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator 1st range

Measurement Range:

+0.0 to 300.0 amperes, dc single indicator 1st range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

4 threaded stud

Special Features:

Panel for which designed is nonmagnetic.

Special Markings:

+v, -v, +a, -a at terminals

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Drawing iaw mil-v-5622

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0