

View Online at <https://aerobasegroup.com/nsn/6625-00-570-5717>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.850 inches

**Scale Division Quantity:**

60 single indicator all ranges

**Mounting Stud Length:**

0.500 inches

**Overall Diameter:**

3.510 inches

**Mounting Bolt Circle Diameter:**

3.160 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

200.0 microamperes

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.660 inches

**Meter Body Diameter Behind Mounting Flange:**

2.800 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Mounting Facility Type And Quantity:**

3 threaded stud

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+0.0 to 60.0 percent modulation single indicator 3rd range

**Mounting Stud Diameter:**

0.138 inches

**Features Provided:**

Zero adjuster

**Circuit Attachment Method And Quantity:**

2 binding post

**Special Features:**

Ruggedized. Featgpanel for which designed is nonmagnetic. Circuit construction type is non electronic.

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0