

View Online at <https://aerobasegroup.com/nsn/6625-00-578-5340>

Circuit Current For Which Designed:

Dc

Overall Length:

3.680 inches

Overall Height:

6.460 inches

Overall Width:

6.460 inches

Environmental Protection:

Dustproof

Furnished Items And Quantity:

Shunt, external, w/5 ft leads, westinghouse elec corporation part no. 8703931 type g switchboard, shunt, external, w/5 ft leads, westinghouse elec corporation part no. 87039340, type o switchboard, shunt, external w/5 ft leads 1 westinghouse elec corporation part no. 2826418, type o switchboard

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

3.430 inches

Meter Body Width Behind Mounting Flange:

5.430 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

1 flange

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

+0.0/+600.0 amperes, dc single indicator 3rd range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

5.430 inches

Features Provided:

Magnetic shield

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 binding post

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set electronic

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0