

View Online at <https://aerobasegroup.com/nsn/6625-00-578-5345>

Circuit Current For Which Designed:

Dc

Overall Length:

1.350 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.040 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.670 inches

Overall Height:

3.940 inches

Overall Width:

4.250 inches

Mounting Hole Diameter:

0.138 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

200.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.110 inches

Meter Body Diameter Behind Mounting Flange:

3.250 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Measurement Range:

+0.0 to 50.0 volts, dc single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 binding post

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0