NSN 6625-00-580-1186

Ammeter - Page 1 of 2

Ac

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-580-1186

| Dielectric Withstanding Voltage In Volts: |
|---|
| 3000.0 |
| Overall Length: |
| 2.820 inches |
| Mounting Hole Diameter: |
| Between 0.143 inches and 0.157 inches |
| Scale Division Quantity: |
| 50 single indicator single range |
| Overall Diameter: |
| 3.510 inches |
| Environmental Protection: |
| Dustproof |
| Mounting Bolt Circle Diameter: |
| 3.160 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 2.420 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.800 inches |
| Movement Type: |
| Moving iron vane |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 3 screw and 3 unthreaded hole |

Scale Graduation Type:

Linear single indicator single range

NSN 6625-00-580-1186

Ammeter - Page 2 of 2



| Measurement Range: |
|--|
| +0.0/+10.0 amperes, ac single indicator single range |
| Scale Selection Method: |
| Switch |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 solderless lug |
| Special Features: |
| Rated freq 60hz |
| Material: |
| Steel |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Surface Treatment: |
| Enamel semigloss |
| Style Designator: |
| Round flush mtg |
| Test Data Document: |
| 31349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 31349-mil-m-10304/14 government specification |
| Fsc Application Data: |
| Test set electronic |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| A310a0 |
| |
| |