Fixed Inductance Standard - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-580-1488

2 Freminal Type: Plug Overall Length: 4.500 inches Frequency Rating: Between 45.0 megahertz and 75.0 megahertz Overall Diameter: 3.500 inches Coverall Diameter: 3.500 inches 3.500 inches Coverall Diameter: 3.500 inches Coverall Diameter: 3.500 inches 3.500	Terminal Quantity:			
Ferminal Type:PlugOverall Length:4.500 inchesFrequency Rating:Between 45.0 megahertz and 75.0 megahertzOverall Diameter:3.500 inchesSoob inchesCase Material:SteelMounting Configuration:PlugInductance Rating:0.1 microhenriesAccuracy Range In Percent:-2.0/+2.0Sheff Life:N/aDint Of Measure:Punction:Na<				
PlugOverall Length:4.500 inchesFrequency Rating:Between 45.0 megahertz and 75.0 megahertzOverall Diameter:3.500 inchesBase Material:SteelMounting Configuration:PlugInductance Rating:0.1 microhenriesAccuracy Range In Percent:-2.0/+2.0Sheft Life:NaDint of Measure:Punction:No				
Overall Length:4.500 inchesFrequency Rating:Between 45.0 megahertz and 75.0 megahertzOverall Diameter:3.500 inchesCase Material:SteelMounting Configuration:PlugInductance Rating:0.1 microhenriesAccuracy Range In Percent:-2.0/+2.0Shelf Life:N/aUnit Of Measure:Demilitarization:No				
4.500 inches Frequency Rating: Between 45.0 megahertz and 75.0 megahertz Overall Diameter: 3.500 inches Case Material: Steel Mounting Configuration: Plug Inductance Rating: 0.1 microhenries Accuracy Range In Percent: -2.0/+2.0 Sheff Life: N/a Unit Of Measure: - Demilitarization: No				
Frequency Rating:Between 45.0 megahertz and 75.0 megahertzDverall Diameter:3.500 inchesCase Material:SteelMounting Configuration:PlugInductance Rating:0.1 microhenriesAccuracy Range In Percent:-2.0/+2.0Shelf Life:N/aUnit Of Measure:Demilitarization:No				
Between 45.0 megahertz and 75.0 megahertz Overall Diameter: 3.500 inches Case Material: Steel Mounting Configuration: Plug Inductance Rating: 0.1 microhenries Accuracy Range In Percent: -2.0/+2.0 Shelf Life: N/a Unit Of Measure: - - No				
Overall Diameter:3.500 inchesCase Material:SteelMounting Configuration:PlugInductance Rating:0.1 microhenriesAccuracy Range In Percent:-2.0/+2.0Shelf Life:N/aUnit Of Measure:No		negahertz		
3.500 inchesCase Material:SteelMounting Configuration:PlugInductance Rating:0.1 microhenriesAccuracy Range In Percent:-2.0/+2.0Shelf Life:N/aUnit Of Measure:No		-		
Steel Mounting Configuration: Plug Inductance Rating: 0.1 microhenries Accuracy Range In Percent: -2.0/+2.0 Shelf Life: N/a Unit Of Measure: Demilitarization: No				
Mounting Configuration:PlugInductance Rating:0.1 microhenriesAccuracy Range In Percent:-2.0/+2.0Shelf Life:N/aUnit Of Measure:Demilitarization:No	Case Material:			
Plug Inductance Rating: 0.1 microhenries Accuracy Range In Percent: -2.0/+2.0 Shelf Life: N/a Unit Of Measure: Demilitarization: No	Steel			
Inductance Rating: 0.1 microhenries Accuracy Range In Percent: -2.0/+2.0 Shelf Life: N/a Unit Of Measure: Demilitarization: No	Mounting Configuration:			
0.1 microhenries Accuracy Range In Percent: -2.0/+2.0 Shelf Life: N/a Unit Of Measure: Demilitarization: No	Plug			
Accuracy Range In Percent: -2.0/+2.0 Shelf Life: N/a Unit Of Measure: Demilitarization: No	Inductance Rating:			
-2.0/+2.0 Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.1 microhenries			
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Accuracy Range In Percent:			
N/a Unit Of Measure: Demilitarization: No	-2.0/+2.0			
Unit Of Measure: Demilitarization: No	Shelf Life:			
 Demilitarization: No	N/a			
Demilitarization: No	Unit Of Measure:			
Νο				
	Demilitarization:			
Fiiq:	No			
0	Fiig:			
T263-d	T263-d			