

View Online at <https://aerobasegroup.com/nsn/6625-00-580-1929>

**Mounting Type:**

Rack

**Overall Length:**

27.250 inches

**Overall Height:**

18.750 inches

**Overall Width:**

15.000 inches

**Current Type:**

Ac

**Frequency Rating:**

60.0 hertz

**Case Material:**

Aluminum

**Case Surface Treatment:**

Enameled

**Frequency Range Rating:**

+88.000/+140.000 megahertz

**Accessory Component Quantity:**

1 and 1 and 1 and 1 and 1 and 1 and 1 and 1 and 1 and 1

**Accessory Controlling Agency:**

Jetds

**Accessory Identifying Number:**

Cy-1068/u type no. And cg-409/u type no. And ug-201/u type no. And ug-528/u type no. And ug-529/u type no. And sg-1a/arm type no. And pp-348/arm type no. And cy-1069/u type no. And cx-237/u type no. And cx-1290/u type no.

**Joint Electronics Type Designation System Item Name:**

Generator, signal

**Joint Electronics Type Designation System Item Type Number:**

Type no. Sg-1a/arm//

**Internal Battery Accommodation:**

Not included

**Output Impedance Rating:**

26.5 ohms

**Voltage Rating:**

115.0 volts

**Frequency Band Quantity:**

1

**Modulation Type:**

Am

**Accessory Component Name:**

Case; cord; adapter; adapter connector; adapter connector; handbook for; power supply; case; cord; power cable assembly

**Calibration Accuracy Rating:**

Porm 0.15 pct accuracy of calibration

**Crystal Controlled Feature:**

Provided

**Calibrated Signal Output Range:**

0.1 uv to 200000 uv calibrated output

**Signal Output Constancy:**

Porm 0.15 db maximum variation from 30 cycles to 11 kc; porm 0.1 db maximum variation from 9500 cycles to 10.5 kc

**Modulator Location:**

Internal

**Modulated Frequency Rating:**

Between 0.4 kilohertz and 1.0 kilohertz

**Modulation Degree:**

100.0 percent

**Phase:**

Single

**Fsc Application Data:**

Test set, radar, except specially designed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T320-j