

View Online at <https://aerobasegroup.com/nsn/6625-00-580-1929>

Mounting Type:

Rack

Overall Length:

27.250 inches

Overall Height:

18.750 inches

Overall Width:

15.000 inches

Current Type:

Ac

Frequency Rating:

60.0 hertz

Case Material:

Aluminum

Case Surface Treatment:

Enameled

Frequency Range Rating:

+88.000/+140.000 megahertz

Accessory Component Quantity:

1 and 1 and 1 and 1 and 1 and 1 and 1 and 1 and 1 and 1

Accessory Controlling Agency:

Jetds

Accessory Identifying Number:

Cy-1068/u type no. And cg-409/u type no. And ug-201/u type no. And ug-528/u type no. And ug-529/u type no. And sg-1a/arm type no. And pp-348/arm type no. And cy-1069/u type no. And cx-237/u type no. And cx-1290/u type no.

Joint Electronics Type Designation System Item Name:

Generator, signal

Joint Electronics Type Designation System Item Type Number:

Type no. Sg-1a/arm//

Internal Battery Accommodation:

Not included

Output Impedance Rating:

26.5 ohms

Voltage Rating:

115.0 volts

Frequency Band Quantity:

1

Modulation Type:

Am

Accessory Component Name:

Case; cord; adapter; adapter connector; adapter connector; handbook for; power supply; case; cord; power cable assembly

Calibration Accuracy Rating:

Porm 0.15 pct accuracy of calibration

Crystal Controlled Feature:

Provided

Calibrated Signal Output Range:

0.1 uv to 200000 uv calibrated output

Signal Output Constancy:

Porm 0.15 db maximum variation from 30 cycles to 11 kc; porm 0.1 db maximum variation from 9500 cycles to 10.5 kc

Modulator Location:

Internal

Modulated Frequency Rating:

Between 0.4 kilohertz and 1.0 kilohertz

Modulation Degree:

100.0 percent

Phase:

Single

Fsc Application Data:

Test set, radar, except specially designed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-j