

View Online at <https://aerobasegroup.com/nsn/6625-00-580-2653>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.665 inches

Scale Division Quantity:

24 single indicator single range

Overall Diameter:

1.688 inches

Environmental Protection:

Watertight

Furnished Items And Quantity:

Term. Hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

1000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.765 inches

Meter Body Diameter Behind Mounting Flange:

1.500 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Percent x 10 dc voltage; 0; 2; 4; 6; 8; 10; 12

Mounting Facility Type And Quantity:

1 collar and 1 threaded body

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Operating Voltage Rating In Volts:

60.0 dc

Special Features:

Internal zero adjust

Special Markings:

Term. Marked pos and neg

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Conforms to mil-m-3823

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0