

View Online at <https://aerobasegroup.com/nsn/6625-00-580-3684>

Circuit Current For Which Designed:

Ac

Overall Length:

1.844 inches

Mounting Hole Diameter:

0.125 inches

Overall Diameter:

2.531 inches

Mounting Bolt Circle Diameter:

2.316 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+0.000 to 60.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.438 inches

Meter Body Diameter Behind Mounting Flange:

2.062 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Measurement Range:

+0.0 to 150.0 volts, ac single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 binding post

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0