NSN 6625-00-580-4479

Ammeter - Page 1 of 2

Dc

Overall Length: 1.490 inches

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-580-4479

Center To Center Distance Between Mounting Facilities Parallel To Length:

| 2.670 inches |
|--|
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.040 inches |
| Overall Height: |
| 3.940 inches |
| Overall Width: |
| 4.250 inches |
| Scale Division Quantity: |
| 40 single indicator single range |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Sensitivity Rating: |
| 100.0 millivolts |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.110 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 3.250 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Mounting Facility Type And Quantity: |
| 4 flange |
| Measurement Range: |
| -100.0/+100.0 milliamperes, dc single indicator single range |
| Scale Selection Method: |
| Terminal |
| Features Provided: |
| Magnetic shield |
| Circuit Attachment Method And Quantity: |
| 2 binding post |
| |

NSN 6625-00-580-4479

Ammeter - Page 2 of 2



| Style Designator: |
|--|
| Rectangular flush mtg |
| Reference Number Differentiating Characteristics: |
| As differentiated by measurement range per indicator |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig:

. ...

A310a0