

View Online at <https://aerobasegroup.com/nsn/6625-00-580-9889>

Circuit Current For Which Designed:

Ac

Overall Length:

2.770 inches

Mounting Hole Diameter:

0.147 inches

Scale Division Quantity:

20 single indicator single range

Frequency Rating:

400.0 hertz

Overall Diameter:

3.500 inches

Environmental Protection:

Hermetic

Mounting Bolt Circle Diameter:

3.160 inches

End Application:

Support equipment-b-52, f-106, ov-10a, c-5 aircraft. Cobra/attack ah-1j helicopter. Prowler ea-6b aircraft.

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Resonant Reed Quantity:

21

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.930 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+380.0 to 420.0 hertz single indicator single range

Scale Selection Method:

Terminal

Criticality Code Justification:

Feat

Circuit Attachment Method And Quantity:

2 solder pin

Operating Voltage Rating In Volts:

Between 100.0 ac and 130.0 ac

Special Features:

Weapon system essential

Material:

Steel

Style Designator:

Round flush mtg

Fsc Application Data:

Test set electronic equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0