NSN 6625-00-581-2418

Voltmeter - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/6625-00-581-2418 |
|---|
| Circuit Current For Which Designed: |
| Dc |
| Dielectric Withstanding Voltage In Volts: |
| 1500.0 |
| Overall Length: |
| 1.375 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.312 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.312 inches |
| Overall Height: |
| 1.750 inches |
| Overall Width: |
| 1.750 inches |
| Mounting Hole Diameter: |
| 0.125 inches |
| Scale Division Quantity: |
| 10 single indicator single range |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Sensitivity Rating: |
| 1000.0 ohms per volt |
| Dial Scale Marking Color: |
| White single indicator single range |
| Accuracy In Percent: |
| -3.0/+3.0 at full scale single indicator all ranges |
| Meter Depth Behind Mounting Flange: |
| 1.000 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 1.500 inches |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Measurement Range: |
| +0.0/+200.0 volts, dc single indicator single range |
| Features Provided: |
| Magnetic shield |
| Circuit Attachment Method And Quantity: |
| 2 solder stud |
| Special Features: |

Ruggedized

NSN 6625-00-581-2418

Voltmeter - Page 2 of 2



| Sty | ۵ | ח | Pei | 'n | n | a | tn | r | |
|------|---|---|-----|----|-----|---|----|---|--|
| OLY! | | _ | CO | 'y | ••• | u | · | • | |

Rectangular flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0