NSN 6625-00-581-5692

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-581-5692

view Online at https://derobasegroup.com/hish/0025-00-501-5052
Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.850 inches
Mounting Hole Diameter:
Between 0.143 inches and 0.157 inches
Overall Diameter:
3.510 inches
Environmental Protection:
Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight
Mounting Bolt Circle Diameter:
3.160 inches
Furnished Items And Quantity:
Nut 7; washer 5
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
1000.0 ohms per volt
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0 to 2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.660 inches
Meter Body Diameter Behind Mounting Flange:
2.800 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:

External

NSN 6625-00-581-5692

Voltmeter - Page 2 of 2



Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Nonlinear single indicator single range
Measurement Range:
+0.0 to 1.5 kilovolts, dc single indicator single range
Features Provided:
Luminous scale marking and magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Material:
Stainless steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel semigloss
Special Test Features:
Environmentals per mil-std-202
Surface Treatment Specification:
Mil-f-14072 military specification single treatment response
Style Designator:
Round flush mtg
Test Data Document:
81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-m-10304/11 government specification
Fsc Application Data:
Electrical, electronic properties measuring and test instruments
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A310a0

Mil-f-14072 spec.

Mil-std (military Standard):