NSN 6625-00-581-7940

Ammeter - Page 1 of 2

Dc

Overall Length: 2.850 inches

0.150 inches

Mounting Hole Diameter:

Scale Division Quantity:

50 single indicator single range

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-581-7940

| Overall Diameter: |
|---|
| 4.600 inches |
| Mounting Bolt Circle Diameter: |
| 4.125 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Six hole/stud bolt circle |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 2.450 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 3.760 inches |
| Movement Type: |
| Moving iron vane |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 6 unthreaded hole |
| Scale Graduation Type: |
| Linear single indicator single range |
| Measurement Range: |
| +0.0/+50.0 amperes, dc single indicator single range |
| Features Provided: |
| Zero adjuster |

NSN 6625-00-581-7940

Ammeter - Page 2 of 2



| Movement Suspension Method: |
|---|
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Special Markings: |
| Red line at 30 amperes |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

Fiig: A310a0