

View Online at <https://aerobasegroup.com/nsn/6625-00-583-1526>

Overall Length:

3.000 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Vibration Resistance Range In Hertz:

Not rated

Shock Resistance Rating In Gravitational Units:

Not rated

Operating Temperature Range:

Not rated

Average Life Measurement:

Not rated

Basic Shape Style:

Irregular

Maximum Operating Altitude Rating:

Not rated

Inclosure Type:

Encased

Operating Control Method:

Manual

Installation Design:

Module

Control Type:

Local

Circuit Construction Type:

Solid state

Frequency Per Channel:

10.0 megahertz operating channel

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

Not rated

Signal Voltage Rating Per Channel:

Not rated

Overall Gain:

Not rated

Impedance Rating Per Channel:

Not rated

Maximum Continuous Operating Time In Hours:

Not rated

Connection Type And Location:

Receptacle, coaxial top

Connection Contact Type And Quantity:

1 receptacle, coaxial external

External Dc Operating Voltage In Volts:

12.0 single voltage

Criticality Code Justification:

Feat

Special Features:

Critical application-acft: starlifter c-141, intruder ka-6d, prowler ea-6b, sky warrior a-3, sky hawk a-4, intruder ea-6a, corsair ii a-7, hawkeye e-2b, phantom f-4, orion p-3; helicopter: ch-53a/d/e, sea knight h-46; support equipment, b-52 aircraft; fire control system, missile mk 74 (fcs); radio set (an/grc-201); radar and iff systems; cobra dan sys, fps-108; defense support program

Supplementary Features:

Rectifier data, crystal diode, semiconductor, type 1n26, unfiltered output

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A32200