

View Online at <https://aerobasegroup.com/nsn/6625-00-583-1526>

**Overall Length:**

3.000 inches

**Overall Height:**

0.750 inches

**Overall Width:**

0.750 inches

**Vibration Resistance Range In Hertz:**

Not rated

**Shock Resistance Rating In Gravitational Units:**

Not rated

**Operating Temperature Range:**

Not rated

**Average Life Measurement:**

Not rated

**Basic Shape Style:**

Irregular

**Maximum Operating Altitude Rating:**

Not rated

**Inclosure Type:**

Encased

**Operating Control Method:**

Manual

**Installation Design:**

Module

**Control Type:**

Local

**Circuit Construction Type:**

Solid state

**Frequency Per Channel:**

10.0 megahertz operating channel

**Attenuation In Decibels:**

Not rated

**Average Power Rating Per Channel:**

Not rated

**Signal Voltage Rating Per Channel:**

Not rated

**Overall Gain:**

Not rated

**Impedance Rating Per Channel:**

Not rated

**Maximum Continuous Operating Time In Hours:**

Not rated

**Connection Type And Location:**

Receptacle, coaxial top

**Connection Contact Type And Quantity:**

1 receptacle, coaxial external

**External Dc Operating Voltage In Volts:**

12.0 single voltage

**Criticality Code Justification:**

Feat

**Special Features:**

Critical application-acft: starlifter c-141, intruder ka-6d, prowler ea-6b, sky warrior a-3, sky hawk a-4, intruder ea-6a, corsair ii a-7, hawkeye e-2b, phantom f-4, orion p-3; helicopter: ch-53a/d/e, sea knight h-46; support equipment, b-52 aircraft; fire control system, missile mk 74 (fcs); radio set (an/grc-201); radar and iff systems; cobra dan sys, fps-108; defense support program

**Supplementary Features:**

Rectifier data, crystal diode, semiconductor, type 1n26, unfiltered output

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A32200