

View Online at <https://aerobasegroup.com/nsn/6625-00-583-6578>

Overall Length:

24.000 inches

Current Type:

Ac

Frequency Rating:

Between 47.0 hertz and 420.0 hertz

Accessory Components And Quantity:

Divider probes 3, cable assembly 1, adjustable probe compensators 3, probe tips 5, adapters 5

Voltage Rating:

115.0 volts and 230.0 volts

Beam Quantity:

1

Accuracy Range In Percent:

-1.0/+1.0

Screen Size:

6 by 10 centimeters

Sweep Circuits:

Included

Generator Driven Feature:

Included

Sweep Circuit Type:

Horizontal and vertical

Sweep Frequency Range:

+0.000/+100.000 megahertz

Trigger Sweep Polarity Switch:

Included

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

5.0 millivolts peak to peak per centimeter and 5.0 volts peak to peak per centimeter

Input Intensity Modulation Feature:

Provided

Visual Blanking Sensitivity Voltage Rating:

5.0 volts

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.0 megohms

Y-axis Input Impedance Rating:

1.0 megohms

Amplitude Calibrating Voltage Waveform:

Square wave

Camera Recording Device Accommodation:

Provided

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T320-g