

View Online at <https://aerobasegroup.com/nsn/6625-00-585-1158>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

1.830 inches

**Mounting Hole Diameter:**

0.150 inches

**Scale Division Quantity:**

8 single indicator 2nd range

**Overall Diameter:**

4.580 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Mounting Bolt Circle Diameter:**

4.124 inches

**Furnished Items And Quantity:**

Mtg hdw 6

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Six hole/stud bolt circle

**Sensitivity Rating:**

50.0 microamperes

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator all ranges

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.150 inches

**Meter Body Diameter Behind Mounting Flange:**

2.780 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Scale Marking:**

X1000r; 0; 20; 40; 60; 80; 100; pct error; -20; -10; 0; 10; 20

**Mounting Facility Type And Quantity:**

6 screw and 6 unthreaded hole

**Scale Graduation Type:**

Linear single indicator all ranges

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug

**Special Features:**

Ruggedized

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Special Test Features:**

Conforms to mil-m-10304

**Style Designator:**

Round flush mtg

**Supplementary Features:**

1520 ohms resistance

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0