

View Online at <https://aerobasegroup.com/nsn/6625-00-585-1854>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

3.135 inches

Mounting Hole Diameter:

0.130 inches

Frequency Rating:

400.0 hertz

Overall Diameter:

3.510 inches

Environmental Protection:

Hermetic and heat resistant and shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

3.160 inches

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+380.000 to 420.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Resonant Reed Quantity:

21

Accuracy In Percent:

-0.5 to 0.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.250 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Measurement Range:

+380.0 to 420.0 hertz single indicator single range

Scale Selection Method:

Terminal

Circuit Attachment Method And Quantity:

2 solder lug

Operating Voltage Rating In Volts:

Between 100.0 ac and 130.0 ac

Phase:

Single

Special Features:

3.0 watts maximum power consumption

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0