

View Online at <https://aerobasegroup.com/nsn/6625-00-585-1854>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

3.135 inches

**Mounting Hole Diameter:**

0.130 inches

**Frequency Rating:**

400.0 hertz

**Overall Diameter:**

3.510 inches

**Environmental Protection:**

Hermetic and heat resistant and shock resistant and vibration resistant

**Mounting Bolt Circle Diameter:**

3.160 inches

**Indicator Type:**

Vibrating reed

**Installation Design:**

Panel

**Register Quantity:**

1

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Frequency Response Range:**

+380.000 to 420.000 hertz

**Dial Scale Marking Color:**

Black single indicator single range

**Resonant Reed Quantity:**

21

**Accuracy In Percent:**

-0.5 to 0.5 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

2.250 inches

**Meter Body Diameter Behind Mounting Flange:**

2.800 inches

**Movement Type:**

Vibrating reed

**Background Color:**

White single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Measurement Range:**

+380.0 to 420.0 hertz single indicator single range

**Scale Selection Method:**

Terminal

**Circuit Attachment Method And Quantity:**

2 solder lug

**Operating Voltage Rating In Volts:**

Between 100.0 ac and 130.0 ac

**Phase:**

Single

**Special Features:**

3.0 watts maximum power consumption

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0