

View Online at <https://aerobasegroup.com/nsn/6625-00-585-4376>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

2.480 inches

**Mounting Hole Diameter:**

0.150 inches

**Overall Diameter:**

3.510 inches

**Mounting Bolt Circle Diameter:**

Between 3.153 inches and 3.167 inches

**Furnished Items And Quantity:**

Nut3; wahser 3

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Frequency Response Range:**

+25.000 to 125.000 hertz

**Sensitivity Rating:**

4.0 volt-amperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.660 inches

**Meter Body Diameter Behind Mounting Flange:**

2.800 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+0.0 to 8.0 volts, ac single indicator single range

**Features Provided:**

Magnetic shield and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug

**Special Features:**

Ruggedized

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Paint

**Special Test Features:**

Conforms to mil-m-10304

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Elec, elect. Properties measuring and test instruments

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0