

View Online at <https://aerobasegroup.com/nsn/6625-00-585-4950>

Circuit Current For Which Designed:

Dc

Overall Length:

5.740 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.560 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.560 inches

Overall Height:

6.460 inches

Overall Width:

6.460 inches

Scale Division Quantity:

30 single indicator all ranges

Mounting Stud Length:

0.870 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-1.0 to 1.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

3.430 inches

Meter Body Diameter Behind Mounting Flange:

5.430 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0 to 30.0 volts, dc single indicator 1st range

Mounting Stud Diameter:

0.190 inches

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

3 solder stud

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0