NSN 6625-00-585-5288

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-585-5288

Circuit Current For Which Designed:
Dc
Overall Length:
2.650 inches
Mounting Hole Diameter:
Between 0.120 inches and 0.130 inches
Scale Division Quantity:
50 single indicator single range
Overall Diameter:
2.695 inches
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Mounting Bolt Circle Diameter:
2.440 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
150.0 millivolts
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.600 inches
Meter Body Diameter Behind Mounting Flange:
2.210 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External

Scale Graduation Type:

Linear single indicator single range

3 screw and 3 unthreaded hole

Mounting Facility Type And Quantity:

NSN 6625-00-585-5288

Ammeter - Page 2 of 2



+0.0/+500.0 microamperes, dc single indicator single range Features Provided: Zero adjuster Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 solder lug and 2 threaded stud Special Features: Ruggedized Material: Plastic and steel Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg Test Data Document:	
Zero adjuster Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 solder lug and 2 threaded stud Special Features: Ruggedized Material: Plastic and steel Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg	
Movement Suspension Method: Jewel pivot base Circuit Attachment Method And Quantity: 2 solder lug and 2 threaded stud Special Features: Ruggedized Material: Plastic and steel Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg	
Jewel pivot base Circuit Attachment Method And Quantity: 2 solder lug and 2 threaded stud Special Features: Ruggedized Material: Plastic and steel Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg	
Circuit Attachment Method And Quantity: 2 solder lug and 2 threaded stud Special Features: Ruggedized Material: Plastic and steel Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg	
2 solder lug and 2 threaded stud Special Features: Ruggedized Material: Plastic and steel Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg	
Special Features: Ruggedized Material: Plastic and steel Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg	
Ruggedized Material: Plastic and steel Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg	
Material: Plastic and steel Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg	
Plastic and steel Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg	
Nuclear Hardness Critical Feature: Nonhardened Style Designator: Round flush mtg	
Nonhardened Style Designator: Round flush mtg	
Style Designator: Round flush mtg	
Round flush mtg	
-	
Test Data Document:	
81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in spe	ification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	in
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Specification Data:	
81349-mil-m-10304/5 government specification	
Fsc Application Data:	
Test set, elect. Equip.	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A310a0	